

YP 系列電子天平
YP SERIES ELECTRONIC BALANCE

YP 系列電子天平具有流暢新穎的外形設計，體現了對現代理念的追求。全新的設計，使稱重的反應速度更快，穩定更迅速。穩定性和抗干擾性高。

本公司開發的YP系列電子天平還可以根據用戶的要求進行生產。具有強大的靈活性，內建電池盒設計是野外操作的最佳選擇。

Product introduction:

YP series electronic balance has fluent and novel appearance design which reflects the pursuit for modern concept. New design brings faster weighing response, higher stability and stronger anti-interference performance. Our YP series electronic balance can be customized upon user's request. With strong flexibility, it will be the best choice for field operation.

特點:

- 交直流兩用，帶水準儀，液晶背光顯示，稱量反應速度快，高穩定性。
- 傳感器採用獨特的鎖緊裝置，確保天平在運輸起到保護作用。

Feature:

- AC/DC exchangeable, balance level, backlight LCD display, rapid weighing response and high stability.
- Sensor adopts unique locking device, which guarantees protection of the balance during transportation.

功能:

- 系統操作有：計數功能，百分比，自動外部校正，綫性多點校正，配標準砝碼（可選）。
- 具有單位轉換（米制克拉、金盎司等）、穩定度、記憶功能、動物稱重、全量程扣重等多種功能，操作更簡便可靠。
- 內置RS232C輸出接口，可直接連接電腦、印表機等外部設備。

Function:

- System operations: including auto-counting, percentage, automatic calibration, multi-point calibration, standard weights (optional).
- Multiple functions guarantee easy and reliable operation, including unit conversion (metric carat, gold ounce, etc.), stability, memory, full-scale taring.
- Built-in RS232C output interface guarantees direct connection to external equipment such as computer and printer.

型號 Model	稱量範圍 Weighing Range	可讀性精度 Readable Precision	外形尺寸 Outline Dimension	外包裝尺寸 Outline Dimension	電源 Power	稱盤尺寸 Scale Size	淨重 Net weight
YP1002	0-100g	10mg	250X180X60mm	325X245X152mm	交直流電兩用	∅125mm	1kg
YP2002	0-200g	10mg	250X180X60mm	325X245X152mm	交直流電兩用	∅125mm	1kg
YP3002	0-300g	10mg	250X180X60mm	325X245X152mm	交直流電兩用	∅125mm	1kg
YP4002	0-400g	10mg	250X180X60mm	325X245X152mm	交直流電兩用	∅125mm	1kg
YP5002	0-500g	10mg	250X180X60mm	325X245X152mm	交直流電兩用	∅125mm	1kg
YP6002	0-600g	10mg	250X180X60mm	325X245X152mm	交直流電兩用	∅125mm	1kg
YP10002	0-1000g	10mg	250X180X60mm	325X245X152mm	交直流電兩用	∅125mm	1kg
YP 20002	0-2000g	10mg	250X180X60mm	325X245X152mm	交直流電兩用	∅125mm	1kg
YP30002	0-3000g	10mg	250X180X60mm	325X245X152mm	交直流電兩用	∅125mm	1kg
YP2001	0-200g	100mg	250X180X60mm	325X245X152mm	交直流電兩用	∅125mm	1kg
YP4001	0-400g	100mg	250X180X60mm	325X245X152mm	交直流電兩用	∅125mm	1kg
YP5001	0-500g	100mg	250X180X60mm	325X245X152mm	交直流電兩用	∅125mm	1kg
YP6001	0-600g	100mg	250X180X60mm	325X245X152mm	交直流電兩用	∅125mm	1kg
YP8001	0-800g	100mg	250X180X60mm	325X245X152mm	交直流電兩用	∅125mm	1kg
YP10001	0-1000g	100mg	250X180X60mm	325X245X152mm	交直流電兩用	∅125mm	1kg
YP16001	0-1600g	100mg	250X180X60mm	325X245X152mm	交直流電兩用	∅125mm	1kg
YP20001	0-2000g	100mg	250X180X60mm	325X245X152mm	交直流電兩用	∅125mm	1kg
YP30001	0-3000g	100mg	250X180X60mm	325X245X152mm	交直流電兩用	165X165mm	1.3kg
YP40001	0-4000g	100mg	250X180X60mm	325X245X152mm	交直流電兩用	165X165mm	1.3kg
YP50001	0-5000g	100mg	250X180X60mm	325X245X152mm	交直流電兩用	165X165mm	1.3kg
YP60001	0-6000g	100mg	250X180X60mm	325X245X152mm	交直流電兩用	165X165mm	1.3kg
YP80001	0-8000g	100mg	250X180X60mm	325X245X152mm	交直流電兩用	165X165mm	1.3kg
YP 100001	0-10000g	100mg	300X120X160mm	356X310X165mm	交直流電兩用	255X190mm	3.2kg
YP150001	0-15000g	100mg	300X120X160mm	356X310X165mm	交直流電兩用	255X190mm	3.2kg
YP200001	0-20000g	100mg	300X120X160mm	356X310X165mm	交直流電兩用	255X190mm	3.2kg
YP300001	0-30000g	100mg	300X120X160mm	356X310X165mm	交直流電兩用	255X190mm	3.2kg
YP 1000	0-1000g	1g	250X180X60mm	325X245X152mm	交直流電兩用	∅125mm	1kg
YP 2000	0-2000g	1g	250X180X60mm	325X245X152mm	交直流電兩用	∅125mm	1kg
YP 3000	0-3000g	1g	250X180X60mm	325X245X152mm	交直流電兩用	165X165mm	1kg
YP 6000	0-6000g	1g	250X180X60mm	325X245X152mm	交直流電兩用	165X165mm	1kg
YP 10000	0-10000g	1g	300X120X160mm	356X310X165mm	交直流電兩用	255X190mm	3.2kg
YP 15000	0-15000g	1g	300X120X160mm	356X310X165mm	交直流電兩用	255X190mm	3.2kg
YP 20000	0-20000g	1g	300X120X160mm	356X310X165mm	交直流電兩用	255X190mm	3.2kg
YP 30000	0-30000g	1g	300X120X160mm	356X310X165mm	交直流電兩用	255X190mm	3.2kg

大稱量YP電子天平
LARGE SCALE YP ELECTRONIC BALANCE



大稱量YP電子天平具有流暢新穎的外型，全新的設計，使稱重的反應速度更快，穩定更迅速。獨特的金屬底座及機械構造，確保了天平的穩定性，增加了天平的抗干擾性。交直流兩用，便于攜帶和野外操作。同時，本公司還可以根據客戶的要求進行特殊規格生產。

Product introduction:

Large-scale YP series electronic balance has fluent and novel appearance as well as new design, which bring faster weighing response. Unique metal base and mechanical structure guarantee higher stability and stronger anti-interference performance. AC/DC exchangeable for portability and field operation.

Besides, we can also customize special specifications upon customer's request.

特點:

- 獨特的外型設計使產品具有高穩定性，背光液晶顯示屏，使操作者視覺更舒適。
- 內置RS232C輸出接口、交直流兩用。

Feature:

- Unique appearance design allows high stability; backlight LCD display brings more comfortable visual sense to operator.
- Built-in RS232C output interface; AC/DC exchangeable

功能:

- 具有多種計量單位轉換、計數、百分比、校準多點選擇，記憶以及動物稱量功能。
- 內置的RS232C輸出接口可以與電腦、印表機等設備連接使用。

Function:

- Multiple functions including unit conversion, auto-counting, percentage, multi-point calibration, memory and animal weights.
- Built-in RS232C output interface guarantees direct connection to external equipment such as computer and printer.

型號 Model	稱量範圍 Weighing Range	可讀性精度 Readable Precision	外形尺寸 Outline Dimension	外包裝尺寸 Outline Dimension	電源 Power	稱盤尺寸 Scale Size
YP 40000	0-40000g	1g	530X300X680mm	840X470X220mm	交直流電兩用	300X400mm
YP 50000	0-50000g	1g	530X300X680mm	840X470X220mm	交直流電兩用	300X400mm
YP 60000	0-60000g	1g	530X300X680mm	840X470X220mm	交直流電兩用	300X400mm
YP 100000	0-100000g	1g	530X300X680mm	840X470X220mm	交直流電兩用	300X400mm
YP 150000	0-150000g	1g	530X300X680mm	840X470X220mm	交直流電兩用	300X400mm
YP200000	0-200000g	1g	530X300X680mm	840X470X220mm	交直流電兩用	300X400mm
YP300000	0-300000g	1g	530X300X680mm	840X470X220mm	交直流電兩用	300X400mm
*YP50000-10	0-50000g	10g	530X300X680mm	840X470X220mm	交直流電兩用	500X400mm
*YP60000-10	0-60000g	10g	530X300X680mm	840X470X220mm	交直流電兩用	500X400mm
*YP100000-10	0-100000g	10g	530X300X680mm	840X470X220mm	交直流電兩用	500X400mm
*YP150000-10	0-150000g	10g	530X300X680mm	840X470X220mm	交直流電兩用	500X400mm
*YP200000-10	0-200000g	10g	530X300X680mm	840X470X220mm	交直流電兩用	500X400mm
*YP300000-10	0-300000g	10g	530X300X680mm	840X470X220mm	交直流電兩用	500X400mm
*YP500000-10	0-500000g	10g	530X300X680mm	840X470X220mm	交直流電兩用	500X400mm
*YP100000-50	0-100000g	50g	530X300X680mm	840X470X220mm	交直流電兩用	500X400mm
*YP150000-50	0-150000g	50g	530X300X680mm	840X470X220mm	交直流電兩用	500X400mm
*YP200000-50	0-200000g	50g	530X300X680mm	840X470X220mm	交直流電兩用	500X400mm

注：帶*以客戶訂單生產 Note: * means customized as per customer's order.